



## **TECHNICAL DATA SHEET**

### **A-A-208**

#### **Ink, Marking, Stencil (Porous and Non-Porous Surfaces)**

**Product:** Formulated for marking glass, plastics, metal film, foil and other nonporous substrates, as well as porous substrates. This ink has excellent resistance to petroleum solvents and trichlorethylene. A-A-208 can be used for marking oily auto parts. Meets CID A-A-208B Types I & IV.

#### **Specifications:**

**Applications:** Rubber stamp from cloth covered felt stamp pad.

Stencil roller with pad or brush, may also be used in airbrush.

**Viscosity:** 38 cps

**Specific Gravity:** 1.20

**Weight Per Gallon:** 10.0 lbs.

**Flash Point:** 46 Deg. F

**Dry Time:** 75 - 105 Seconds.

Variations in temperature and humidity may effect dry time.

**Shelf Life & Storage:** 24 months, stored at normal room temperature.

Ink should be capped tightly after each use.

**Chemical Base:** Solvent.

**Colorant Base:** Pigment.

**Reconditioner:** #2000 Reconditioner.

**Colors:** Black, Gray, Red, Pink, White, Blue, Gold, Yellow, Orange, Green, Brown, Maroon and magenta.

**Availability:** Quarts & Gallons.

**Statement Of Liability:** Neither the manufacturer nor seller shall be liable for any injury, loss or damage arising out of the use of this product. The only obligations of the manufacturer or seller shall be to replace any quantity of this product found to be defective or, at the option of the seller or manufacturer, to refund the purchase price. The purchaser or user of this product should, before use of the product determine whether it is suitable for that use. The user assumes all risk and liability in connection with that use. The foregoing is in lieu of all other warranties expressed or implied.