

MACH-DYNAMICS  
494 Main Street  
Susquehanna, PA 18847  
(775) 278-9308 Fax (775) 599-4585



## TECHNICAL DATA SHEET

Page 1 of 2

### A-A-208B TYPE II (TT-I-1795A)

#### Product:

Formulated for stenciling on porous substrates. This ink can be applied by roller with pad or brush and by fountain brush or roller. Is resistant to alcohols. Meets CID A-A-208B Type II.

#### Specifications:

#### Applications:

Stencil roller with pad or brush and fountain brush or roller.

Viscosity: 25 cps

Specific Gravity: 0.90

Weight Per Gallon: 7.5 lbs.

Flash Point: 105 to 135 Deg. F

Dry Time: 3 - 5 Minutes.

Variations in temperature and humidity may effect dry time.

Shelf Life & Storage: 12 months, stored at normal room temperature.  
Ink should be capped tightly after each use.

Chemical Base: Solvent.

Colorant Base: Pigment.

Reconditioner: #4130 Reconditioner.

Colors: Black, White, Blue

Availability: Quarts & Gallons.

#### Statement Of Liability:

Neither the manufacturer nor seller shall be liable for any injury, loss or damage arising out of the use of this product. The only obligations of the manufacturer or seller shall be to replace any quantity of this product found to be defective or, at the option of the seller or manufacturer, to refund the purchase price. The purchaser or user of this product should, before use of the product determine whether it is suitable for that use. The user assumes all risk and liability in connection with that use.

The foregoing is in lieu of all other warranties expressed or implied.

MACH-DYNAMICS  
494 Main Street  
Susquehanna, PA 18847  
(775) 278-9308 Fax (775) 599-4585

## TECHNICAL DATA SHEET

Page 2 of 2

### A-A-208B TYPE II (TT-I-1795A)

#### RE-CONDITIONERS

Most inks occasionally require thinning, especially the rapid air drying varieties. Re-conditioners are designed to dilute the ink, or replace evaporated solvents, without changing drying and other properties of the ink.

Ink in stamp pads will lose solvents when the pads are left open. It is recommended that you use small amounts of re-conditioner on the stamp pad as necessary and especially before storage. Stamp pads should be stored in tightly sealed plastic bags, when not in use.

#### Statement Of Liability:

Neither the manufacturer nor seller shall be liable for any injury, loss or damage arising out of the use of this product. The only obligations of the manufacturer or seller shall be to replace any quantity of this product found to be defective or, at the option of the seller or manufacturer, to refund the purchase price. The purchaser or user of this product should, before use of the product determine whether it is suitable for that use. The user assumes all risk and liability in connection with that use.

The foregoing is in lieu of all other warranties expressed or implied.

**End of Document**