

TECHNICAL DATA SHEET

MACH-DYNAMICS
Cage Code 1RRC4

A-A-208 Type III Aerosol READ MSDS BEFORE USE.

Surface must be free of grease, rust and dirt.

Spray in a well ventilated area.

Protect objects from over spray.

For best results use at 70 degree Fahrenheit.

If can is chilled place in warm water.

Shake back and forth and with a rotary motion.

Swirl the agitator around bottom seam of can.

Spray no closer than 10 inches from surface being coated.

Move can with short strokes.

SHAKE CAN BETWEEN PASSES.

Open and shut valve completely.

Turn upside down and spray a short jet of clear gas after each job.

Health 2 , Flammability 4, Reactivity 0, Pers. Prot'n G

Health: Harmful or fatal if swallowed. Do not induce vomiting. Flush eyes with warm water for 15 minutes, consult a physician immediately.

Flammability: Keep away from heat, sparks or flames.

Reactivity: Stable at normal temperatures, incompatible with alkalines, strong acids and oxidizing materials.

Protective Equipment: Use splash goggles, rubber gloves, synthetic apron and vapor respirator.

KEEP OUT OF REACH OF CHILDREN.

THIS IS NOT AN ARCHITECTURAL COATING.

FOR INDUSTRIAL USE ONLY.