



TECHNICAL DATA SHEET

Page 1 of 1

CELLULOSE NITRATE LACQUER MIL-L-10287B

PRODUCT DESCRIPTION:

A cellulose nitrate lacquer used in both the manufacture of small arms ammunition for identification purpose and in the assembly of small arms ammunition primers.

Intended Use: This lacquer is used in both the manufacture of small arms ammunition for identification purposes and is applied over gilding metal, and in assembly of small arms ammunition primers.

TYPICAL PROPERTIES:

COLORS	FED-STD- 595B
TYPE I:	Opaque
TYPE II:	Semi-Transparent
DRYING TIME:	Within 4 Minutes
SOLIDS	30 - 35%

APPLICATION & REDUCTION:

May be applied by brush, roll, spray or dip tank application. Brush and roll small areas only due to quick drying characteristics. Thin with TT-T-266D up to 1/2 pint per gallon to a viscosity of 40-50 centipose or as needed for proper application.

PRECAUTIONS:

Store at room temperature

Contents are **FLAMMABLE**.

Keep away from heat and open flame.

For Industrial Use Only - **KEEP OUT OF THE REACH OF CHILDREN.**

Do not take internally.

Avoid breathing vapor or mist.

Do not use in tank or pit without proper protection.

READ Material Safety Data Sheet before use of this product.