



TECHNICAL DATA SHEET

Page 1 of 1

WALKWAY COMPOUND - NON-SLIP MIL-W-5044C

PRODUCT

A non-slip walkway coating with non-skid properties.

DESCRIPTION

MIL-W-5044C Walkway Coating is a single component non-slip walkway compound coating for use on walkways of exterior aircraft surfaces. Type II contains grit for added non-skid properties and is for brushing and rolling applications only.

PROPERTIES

Colors	All Per FED-STD-595B
Type I	Smooth - No Grit
Type II	Grit Added
Finish	Flat or Semi-Gloss
Solids (Weight)	52 - 55%
Drying Times:		
Tack Free	15 Minutes
Recoat	30 Minutes
Full Hardness	24 Hours

APPLICATION:

Apply by brush or roll methods. Thin with MIL-T-81772B Type III Reducer or TT-X-916 Xylene as needed to facilitate proper flow.

Apply in multiple coats as needed for proper film build.

Do not apply heavy coats. Do not over brush Type II so that an even distribution of the grit is achieved.

USES:

- (1). Exterior Aircraft Walkways
- (2). Heavy Traffic Areas
- (3). Non-Slip Requirements

ADVANTAGES:

- (1). Non-Slip
- (2). Air Dry
- (3). Fast Dry
- (4). Durable