

MACH-DYNAMICS
3870 La Sierra Avenue, Suite 212
Riverside, CA 92505
(951) 515-3748 Fax (775) 599-4585



TECHNICAL DATA SHEET

Page 1 of 2

SEMI GLOSS ENAMEL TT-E-529G

PRODUCT

A semi-gloss, alkyd enamel formulated for interior and exterior metal and wood surfaces. This coating is primarily used as a medium dry finish coat on equipment.

PROPERTIES

COLORS Fed Std. 595B
GRIND Not Under 6
SPECULAR GLOSS 15- 25 @ 60 Deg
VISCOSITY 67 - 77 KU

DRYING TIME AT 75? F:

SET-TO-TOUCH Within 2 Hours
DRY HARD Within 8 Hours
FULL HARDNESS Within 72 Hours

ADVANTAGES

- (1). Interior / Exterior Use.
- (2). Semi-Gloss Finish
- (3). Meets TT-E-529G
- (4). Full Color Range, FED-STD-595 Colors
- (5). Fast Production Time.

USES: Steel, Machinery, Tanks, Wood, Equipment, and Towers.

MACH-DYNAMICS
3870 La Sierra Avenue, Suite 212
Riverside, CA 92505
(951) 515-3748 Fax (775) 599-4585

TECHNICAL DATA SHEET

Page 2 of 2

SEMI GLOSS ENAMEL TT-E-529G

APPLICATION & INDUCTION:

TT-E-529 Enamels can be applied by conventional or airless spray application. For spraying, thin up to 10% or as needed with Xylene. For brushing, use as is or with minimum thinning.

SURFACE PREPARATION:

Surface must be clean and free of all contamination before application. Prime per specification instructions.

STEEL:

Surface must be clean and free of all oil, grease and foreign material. Badly rusted or pitted steel should be cleaned by commercial sandblasting and primed the same day.

PRECAUTIONS:

Contents are FLAMMABLE.

Keep away from heat and open flame.

KEEP OUT OF THE REACH OF CHILDREN.

Do not take internally.

Avoid breathing vapor or mist.

Do not use in tank or pit without proper protection.

READ Material Safety Data Sheet before use of this product.

END OF DOCUMENT