

MACH-DYNAMICS  
 494 Main Street  
 Susquehanna, PA 18847  
 (775) 278-9308  
 Fax (775) 599-4585  
<http://www.mach-dynamics.com/>  
[sales@mach-dynamics.com](mailto:sales@mach-dynamics.com)

## MIL-C-7024D Type III

<b>Property</b>	<b>Typical Value</b>	<b>Specification</b>	<b>Test Method</b>
Distillation Range, °F			ASTM D 86
Initial Boiling Point	424	420 min	
50%	435.6	430 – 450	
End Point	466.5	450 - 475	
Specific Gravity at 15 °C	0.778	0.775 – 0.785	ASTM D 4052
Corrosion, 3 h at 50 °C	1A	1 max	ASTM D 130
Viscosity at 40 °C, cSt	2.54	2.37 – 2.57	ASTM D 445
Color, Saybolt	+25	+25 min	ASTM D 156
Freezing Point, °F	<-68	-65 max	ASTM D 2386
Aniline Point	194	190 min	ASTM D 611
Flash Point, °F	184	175 min	ASTM D 56
Acidity of Distillation Residue	Neutral	Neutral	ASTM D 1093
API Gravity	51.59		ASTM D 1298

Revised: 06/18/02

Notice: Since the conditions of handling and use are beyond our control, we make no guarantee of results, nor is any of the above information to be taken as a license to operate under, or recommendation to infringe upon, any patent. The information contained herein is, to the best of our knowledge and belief, accurate, but we assume no liability for damages or penalties resulting from use of or reliance on this information.