

MSDS# 6050-01

MATERIAL SAFETY DATA SHEET

SECTION 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NUMBER: **A-A-56032**
PRODUCT COLOR: All Black, All White, All Gray, Blue, Blue 33182, Blue 33392, Violet, Clear, Brown 30117, Green 34031, Green 14403, Green 34540, Orange 68271, Gold, Silver
CHEMICAL NAME: Mixture
FORMULA: Proprietary Mixture
HMIS HAZARD CODE H:2 F:1 R:1

MACH-DYNAMICS
3410 La Sierra Ave, F191
Riverside, CA 92503
Phone (775) 278-9308 Fax (775) 599-4585

Emergency Telephone Number:

TRANSPORTATION: CHEMTREC (800) 424-9300

SECTION 2. COMPOSITION/INFORMATION ON INGREDIENTS

Listed below are all the hazardous ingredients, with CAS# and hazard data, of this mixture, pursuant to NJ Admin Code Title 8, Chap 59 (NJ Worker and Community Right to Know Act) and the Special Health Hazard Substance List (NJAC 8:59-10). This exceeds Federal OSHA requirements. NJ requires that the five most predominant ingredients be listed, which may include a Trade Secret Registry Number (NJTSRN) to cover those nonhazardous top five ingredients not specifically listed. Available health hazard and physical property information concerning the mixture is furnished in this data sheet. In the event of a medical emergency, specific chemical information will be made immediately available to a treating physician or nurse.

<u>Ingredient(s)</u>	<u>CAS Number</u>	<u>Weight %</u>	<u>OSHA TLV</u>	<u>ACGIH TLV</u>
NJTSRN: 6050BLK				

SECTION 3. HAZARDS IDENTIFICATION

Emergency Overview: As noted in the preface to published values adopted by the ACGIH, TLV's represent "conditions under which it is believed that nearly all workers may be repeatedly exposed day after day without adverse effect. Because of wide variation in individual susceptibility however, a small percentage of workers may experience discomfort from some substances at concentrations at or below the threshold limit; a smaller percentage may be affected more seriously by aggravation of a pre-existing condition or by development of occupational illness."

MSDS# 6050-01

Potential Health Effects

- INGESTION: Slightly irritating to gastrointestinal tract. Can cause headache, diarrhea, drowsiness, breathing difficulties, nausea, vomiting.
- EYES: Moderately irritating or other symptoms (redness, blurred vision, etc) persisting more than seven days with reversible corneal opacity.
- SKIN: Slightly irritating. Prolonged or widespread contact may lead to defatting or dermatitis.
- INHALATION: Slightly irritating to nasal and respiratory tracts. Can cause headache, drowsiness, dizziness, breathing difficulties, nausea.

SECTION 4. FIRST AID MEASURES

- INGESTION: Currently available information does not contraindicate induction of vomiting. Induce vomiting, if conscious, as directed by medical personnel. Seek medical attention.
- EYES: Flush immediately with water for at least 15 minutes or until medical personnel indicate to stop. Seek medical attention.
- SKIN: Remove contaminated clothing. Thoroughly wash with soap and large amounts of water. Seek medical attention.
- INHALATION: Remove to fresh air. Restore breathing. Treat symptomatically. Seek medical attention.

SECTION 5. FIREFIGHTING MEASURES

- FLASH POINT (°F, TCC): >240
- FLAMMABLE LIMITS: LEL: unknown UEL: unknown
LEL value reported is lowest listed for any ingredient in mixture
- EXTINGUISHING MEDIA: Water fog, Multipurpose foam, Dry chemical, CO2
- SPECIAL FIREFIGHTING PROCEDURES:
Fight as volatile liquid fire.

MSDS# 6050-01

SECTION 6. ACCIDENTAL RELEASE MEASURES

SPILL OR LEAK PROCEDURES: Secure area and remove all sources of ignition and heat. Prevent additional discharge of material. Absorb small spills with sand, filter-aid, vermiculite or other inert absorbent material. For large spills, prevent material from entering sewers or water courses. Contain spill with sand, or earth dikes. Recover as much as possible by pumping. Treat remainder as small spill. Dispose of waste in accordance with applicable government regulations. Wear chemical goggles, gloves, boots, and protective clothing. Wear respirator if necessary.

SECTION 7. HANDLING AND STORAGE

STORAGE TEMPERATURE: 40 - 90° F

SHELF LIFE: Recommended use within 12 months.
Refrigeration will extend shelf life.

HANDLING AND STORAGE PRECAUTIONS: Store in tightly closed or properly vented container away from heat, sparks, open flame, or strong oxidizing agents. Containers must be properly grounded and adequate ventilation provided. Unscrew all caps slowly. Do not unscrew entirely until all pressure has been completely released.

REPAIR & MAINTENANCE OF CONTAMINATED EQUIPMENT: Handle all equipment containing liquid mixture as reported on this MSDS. Equipment with "dried mixture" must be handled with the same care as other dried organic coatings. All cleaning material should be handled according to their instructions and their MSDSs.

OTHER PRECAUTIONS: Use only with adequate ventilation. Dispose of "empty" containers promptly and properly.

SPECIAL PRECAUTIONS: None

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE PROTECTION: Eye protection such as chemical splash goggles and/or face shield must be worn when possibility exists for eye contact due to splashing or spraying liquid, airborne particles or vapor. Contact lenses must not be worn.

SKIN PROTECTION: Depending on the conditions of use, protective gloves, clothing, boots, head and face protection should be worn.

RESPIRATORY/VENTILATION: If workplace exposure limits of product or any component is exceeded, NIOSH/MSHA approved respiratory protection must be used.

ENGINEERING CONTROLS: Provide local exhaust or general room ventilation to minimize exposure to vapors.

MSDS# 6050-01

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL FORM:	Liquid
ODOR:	Mild
BOILING POINT (°F):	>400
VAPOR PRESSURE (mm Hg):	<0.1
VAPOR DENSITY (Air=1):	approx 5.6
SOLUBILITY IN WATER:	Moderate
SPECIFIC GRAVITY (H ₂ O=1):	1.20
% VOLATILE BY VOLUME:	approx 20
EVAPORATION RATE (nBuAcet=1):	<0.01

SECTION 10. REACTIVITY

STABLE:	No - Keep away from heat above 150°F; Irreversible polymerization will cause heat buildup
HAZARDOUS POLYMERIZATION:	Yes
INCOMPATIBILITIES:	Strong oxidizing agents, strong acids, strong bases, alkali metals, halogens
DECOMPOSITION PRODUCTS:	CO, CO ₂ , Organic Combustion Products, Oxides of Nitrogen, Metal Oxide Fumes

SECTION 11. TOXICOLOGICAL INFORMATION

No Data Available

SECTION 12. ECOLOGICAL INFORMATION

No Data Available

SECTION 13. DISPOSAL CONSIDERATIONS

Consult Federal, State, and Local Regulations for accepted procedures of disposal, and any reporting or notification requirements.

MSDS# 6050-01

SECTION 14. TRANSPORTATION INFORMATION

DOT SHIPPING NAME: None
DOT HAZARD CLASS: Not Regulated
UN NUMBER: None
DOT LABEL: None Required
FREIGHT CLASS: 55

SECTION 15. REGULATORY INFORMATION

TSCA STATUS: Listed

OTHER REGULATORY:

<u>Ingredient(s)</u>	<u>SARA 302</u>	<u>SARA 313</u>	<u>RECRA</u>	<u>PROP 65</u>
NJTSRN: 6050BLK	No	No	No	No

SECTION 16. OTHER INFORMATION

REASON FOR ISSUE: Correction in Section 10
PREPARED BY: Tom Sweet
TITLE:
APPROVAL DATE: 06/24/2008
SUPERCEDES DATE: 10/19/2007

DISCLAIMER OF LIABILITY

As the conditions or methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for any use of the material described in this MSDS. Information contained herein is given in good faith and believed to be true and accurate, but all statements or suggestions are made without warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material, or results to be obtained from the use thereof. All of the ingredients in this product that are considered to present a health hazard as defined in Appendix A of the OSHA "Hazard Communication" standard (29CFR 1910.1200) are listed in Section II. All of the information given, including ingredient identification, CAS Number, and quantity, is proprietary information, which has been provided in order to meet the objective of the "Hazard Communication" standard. This formulation information is confidential, and only to be disclosed in accordance with Federal and State safety and health regulations. Permission to disclose any ingredient information for any other purpose is neither given nor implied.

MSDS# 6050-11

MATERIAL SAFETY DATA SHEET

SECTION 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NUMBER: **A-A-56032** Catalyst
PRODUCT COLOR: All Black, All White, All Gray, Blue, Blue 33182, Blue 33392, Violet, Clear, Brown 30117, Green 34031, Green 14403, Green 34540, Orange 68271, Gold, Silver
CHEMICAL NAME: Mixture
FORMULA: Proprietary Mixture
HMIS HAZARD CODE H:2 F:1 R:0

MACH-DYNAMICS
3410 La Sierra Ave, F191
Riverside, CA 92503
Phone (775) 278-9308 Fax (775) 599-4585

Emergency Telephone Number:

TRANSPORTATION: CHEMTREC (800) 424-9300

SECTION 2. COMPOSITION/INFORMATION ON INGREDIENTS

Listed below are all the hazardous ingredients, with CAS# and hazard data, of this mixture, pursuant to NJ Admin Code Title 8, Chap 59 (NJ Worker and Community Right to Know Act) and the Special Health Hazard Substance List (NJAC 8:59-10). This exceeds Federal OSHA requirements. NJ requires that the five most predominant ingredients be listed, which may include a Trade Secret Registry Number (NJTSRN) to cover those nonhazardous top five ingredients not specifically listed. Available health hazard and physical property information concerning the mixture is furnished in this data sheet. In the event of a medical emergency, specific chemical information will be made immediately available to a treating physician or nurse.

<u>Ingredient(s)</u>	<u>CAS Number</u>	<u>Weight %</u>	<u>OSHA TLV</u>	<u>ACGIH TLV</u>
Xylene (mixed isomers)	1330-20-7	3-7	100ppm	100ppm
Methyl Isobutyl Ketone	108 10-1	3-7	50ppm	50ppm
Formaldehyde	50-00-0	0-1	0.75ppm	1ppm
NJTSRN: 6050BLK				

SECTION 3. HAZARDS IDENTIFICATION

Emergency Overview: As noted in the preface to published values adopted by the ACGIH, TLV's represent "conditions under which it is believed that nearly all workers may be repeatedly exposed day after day without adverse effect. Because of wide variation in individual susceptibility however, a small percentage of workers may experience discomfort from some substances at

MSDS# 6050-11

concentrations at or below the threshold limit; a smaller percentage may be affected more seriously by aggravation of a pre-existing condition or by development of occupational illness."

Potential Health Effects

- INGESTION: Slightly irritating to gastrointestinal tract. Can cause headache, drowsiness, dizziness, breathing difficulties, nausea, vomiting.
- EYES: Moderately irritating or other symptoms (redness, blurred vision, etc) persisting more than seven days with reversible corneal opacity.
- SKIN: Moderately irritating. Sensitizer. Prolonged or widespread contact may lead to irritation, defatting or dermatitis; absorption may lead to headache, drowsiness, nausea, breathing difficulties.
- INHALATION: Slightly irritating to nasal and respiratory tracts. Can cause headache, drowsiness, dizziness, breathing difficulties, nausea, unconsciousness.

SECTION 4. FIRST AID MEASURES

- INGESTION: Do not induce vomiting. Aspiration of material can cause chemical pneumonitis, which can be fatal. Seek medical attention.
- EYES: Flush immediately with water for at least 15 minutes or until medical personnel indicate to stop. Seek medical attention.
- SKIN: Remove contaminated clothing. Thoroughly wash with soap and large amounts of water. Seek medical attention.
- INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention.

SECTION 5. FIREFIGHTING MEASURES

- FLASH POINT (°F, TCC): >200
- FLAMMABLE LIMITS: LEL: unknown UEL: unknown
LEL value reported is lowest listed for any ingredient in mixture
- EXTINGUISHING MEDIA: Water fog, Multipurpose foam, Dry chemical, CO₂
- SPECIAL FIREFIGHTING PROCEDURES: Fight as volatile liquid fire.

MSDS# 6050-11

SECTION 6. ACCIDENTAL RELEASE MEASURES

SPILL OR LEAK PROCEDURES: Secure area and remove all sources of ignition and heat. Prevent additional discharge of material. Absorb small spills with sand, filter-aid, vermiculite or other inert absorbent material. For large spills, prevent material from entering sewers or water courses. Contain spill with sand, or earth dikes. Recover as much as possible by pumping. Treat remainder as small spill. Dispose of waste in accordance with applicable government regulations. Wear chemical goggles, gloves, boots, and protective clothing. Wear respirator if necessary.

SECTION 7. HANDLING AND STORAGE

STORAGE TEMPERATURE: 40 - 90° F

SHELF LIFE: Recommended use within 12 months.
Refrigeration will extend shelf life.

HANDLING AND STORAGE PRECAUTIONS: Store in tightly closed or properly vented container away from heat, sparks, open flame, or strong oxidizing agents. Containers must be properly grounded and adequate ventilation provided. Unscrew all caps slowly. Do not unscrew entirely until all pressure has been completely released.

REPAIR & MAINTENANCE OF CONTAMINATED EQUIPMENT: Handle all equipment containing liquid mixture as reported on this MSDS. Equipment with "dried mixture" must be handled with the same care as other dried organic coatings. All cleaning material should be handled according to their instructions and their MSDSs.

OTHER PRECAUTIONS: Use only with adequate ventilation. Dispose of "empty" containers promptly and properly.

SPECIAL PRECAUTIONS: None

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE PROTECTION: Eye protection such as chemical splash goggles and/or face shield must be worn when possibility exists for eye contact due to splashing or spraying liquid, airborne particles or vapor. Contact lenses must not be worn.

SKIN PROTECTION: Depending on the conditions of use, protective gloves, clothing, boots, head and face protection should be worn.

RESPIRATORY/VENTILATION: If workplace exposure limits of product or any component is exceeded, NIOSH/MSHA approved respiratory protection must be used.

ENGINEERING CONTROLS: Provide local exhaust or general room ventilation to minimize exposure to vapors.

MSDS# 6050-11

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL FORM:	Liquid
ODOR:	Characteristic
BOILING POINT (°F):	>200
VAPOR PRESSURE (mm Hg):	<0.1
VAPOR DENSITY (Air=1):	approx 5.6
SOLUBILITY IN WATER:	Moderate
SPECIFIC GRAVITY (H ₂ O=1):	1.20
% VOLATILE BY VOLUME:	approx 15
EVAPORATION RATE (nBuAcet=1):	<0.01

SECTION 10. REACTIVITY

STABLE:	Yes
HAZARDOUS POLYMERIZATION:	No
INCOMPATIBILITIES:	Strong oxidizing agents, strong acids, strong bases, alkali metals, halogens
DECOMPOSITION PRODUCTS:	CO, CO ₂ , Organic Combustion Products, Oxides of Nitrogen, Metal Oxide Fumes

SECTION 11. TOXICOLOGICAL INFORMATION

No Data Available

SECTION 12. ECOLOGICAL INFORMATION

No Data Available

SECTION 13. DISPOSAL CONSIDERATIONS

Consult Federal, State, and Local Regulations for accepted procedures of disposal, and any reporting or notification requirements.

MSDS# 6050-11

SECTION 14. TRANSPORTATION INFORMATION

DOT SHIPPING NAME: None
DOT HAZARD CLASS: Not Regulated
UN NUMBER: None
DOT LABEL: None Required
FREIGHT CLASS: 55

SECTION 15. REGULATORY INFORMATION

TSCA STATUS: Listed

OTHER REGULATORY:

<u>Ingredient(s)</u>	<u>SARA 302</u>	<u>SARA 313</u>	<u>RECRA</u>	<u>PROP 65</u>
Xylene (mixed isomers)	No	Yes	U239	No
Methyl Isobutyl Ketone	No	Yes	U161	No
Formaldehyde	Yes	Yes	U122	Yes
NJTSRN: 6050BLK	No	No	No	No

SECTION 16. OTHER INFORMATION

REASON FOR ISSUE: MSDS form revision
PREPARED BY: Tom Sweet
TITLE:
APPROVAL DATE: 06/24/2008
SUPERCEDES DATE: 10/19/2007

DISCLAIMER OF LIABILITY

As the conditions or methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for any use of the material described in this MSDS. Information contained herein is given in good faith and believed to be true and accurate, but all statements or suggestions are made without warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material, or results to be obtained from the use thereof. All of the ingredients in this product that are considered to present a health hazard as defined in Appendix A of the OSHA "Hazard Communication" standard (29CFR 1910.1200) are listed in Section 11. All of the information given, including ingredient identification, CAS Number, and quantity, is proprietary information, which has been provided in order to meet the objective of the "Hazard Communication" standard. This formulation information is confidential, and only to be disclosed in accordance with Federal and State safety and health regulations. Permission to disclose any ingredient information for any other purpose is neither given nor implied.